

DIVYA **PACKAGING MACHINERY**



99041 89177
82009 84237



MANUFACTURERS AND SUPPLIERS OF PACKAGING MACHINERY



All Type Of Packaging Machine

- Box Strapping Machine
- Bag Sealing Machine
- Coding Machine
- Shrink Tunnel Machine
- Induction Sealer Machine
- Pouch Packing Machine
- Liquid Filling Machine
- Pad Printing Machine
- Packaging Materials
- Machinery Parts Mfg.

Website: <https://divyapackagingmachinery.com>

Heavy duty- Semi Automatic Strapping Machine

Features & Specification :

Automatic Power Off., Adjustable cooling time., Adjustable strap tension and length.
Stainless Steel Top and Rust resistance Spares



Specifications:

Power supply	230v. A.C (Single ph).
Strapping speed	1.5 Second / Strap
Max. packing size	Any size
Minimum packing size	60mm
Machine dimensions (LxWxH)mm	895 x 565 x 740 895 x 565 x 505
Max. packing weight	90kg
Max. tension	60kg
Power consumption	1/3 H.P. Single induction
Strap width	6 mm to 15 mm
Machine Weight	100kg Approx 95kg Approx

Applications: Heavy Boxes, Textile., Machine can align with In-feed-out-feed.
Conveyor due to its low table height.

Stretch Wrapping Machine

Features:

- Very fast and economic packing, gives packages/box extra strength.
- Adjustable box stopper for various box sizes, which eliminates pneumatic top holding. Hence no air connection required for holding of Box
- Stretch film tension can be adjustable for tight or loose apply on box.

Specifications:

Voltage (V/Hz)	230v. A.C. (3ph)
Max. Box Size(mm)	750 x 750 x 750 900 x 900 x 900
Motor	1hp/Rotomotive Italy Make Geared Motor
Max. Box weight	40kg 60kg
Machine dimensions (LxWxH)mm	1200 x 650 x 600 1300 x 900 x 450
Stretch roll dispenser	double roll dispenser
Max. Stretch roll Size(mm)	900mm
Counter meter	Double display counter
Wrapping speed	21 turns / minute
Machine Weight	170kg Approx 250kg Approx

Applications: With Pneumatic Pressing Arrangement
For export packing, corrugated boxes packing.
Textile yarns packing on pallets directly, Ceramic products packing.



Box Wrapping Machine

Features:

- Very fast and economic packing, gives packages/box extra strength.
- Adjustable box stopper for various box sizes, which eliminates pneumatic top holding. Hence no air connection required for holding of Box.
- Stretch film tension can be adjustable for tight or loose apply on box.



Specifications:

Power supply	230v. A.C. (3ph)
Max. Box Size(mm)	750 x 750 x 750 1500 x 1500 x 2100
Turntable Motor	0.75kw
Film-rack lift motor	0.18kw
Machine dimensions (LxWxH)mm	1200 x 600 x 600 1510 x 2500 x 2600
Max. packing weight	60kg 2000kg
Max. packing height	900mm 2100mm
Diameter of turntable	600mm 1500mm
Wrapping speed	21 turns / minute Variable
Machine Weight	230kg Approx 530kg Approx

Applications: With Pneumatic Pressing Arrangement
For export packing, corrugated boxes packing.
Textile yarns packing on pallets directly, Ceramic products packing.

Shrink Tunnel Machine

Features : Adjustable Height, Variable speed conveyor,
Can be used at floor height (Detachable stand)

Specifications:

Power supply	440v/50Hz (Three ph)	230v/50Hz (Single ph).
Tunnel Dimensions(mm)	1050x570x1420	1020x400x910
Power consumption	3.7 k.w.	2.5 k.w.
Minimum packing size	300mm x 200mm	180mm x 150mm
Machine dimensions	1050 x 570 x 350	1020 x 400 x 910
Max. packing weight	7kg	5kg
Conveyor speed	0 to 8 Mtr. / Min	
Machine Weight	130kg Approx	100kg Approx

Applications : Stationary, Books, Files, Magazine, Manual, Envelopes ,Xerox Paper, Gift Article, Greeting Card,Trophies,Toys & Games,Computer Consumable , Accessories, PCB, Electrical Components, Dry cell Battery Etc.Pharmaceuticals & Chemical Product Medical Equipments, Cosmetics, Household Articles Industrial, Engineering, Automobile Components Textile & Hardware Articles Multi Packs, Promotional Materials And More Fast Food, Confectionary, Beverages & Dairy Product



Continous Band Sealer Machine

Features & Specification :

Suitable for sealing all kind of Plastic films,Sealing length is unlimited,Reliable sealing quality, Compaq design & can use,Horizontally (Modal : 018) & Vertically (Modal : 22)



Specifications:

Voltage (V/Hz)	230v. A.C. (Single ph)	
Motor Power	50	
Sealing power	300x2	
Speed	0-12	
Temperature range	0-300	
Distance from sealing center	10-40mm	150-270mm
Conveyor Table Size (L x W)mm	840-153	
Overall conveyor loading	4kg	
Dimension(mm)	840 x 380 x 320	840 x 380 x 550
Machine Weight	32kg Approx	37kg Approx

Applications:

For export packing, Special for masala, Pharma, Surgical, Oil industries etc.

Semi Automatic Strapping Machine

Features & Specification :

Automatic Power Off., Adjustable cooling time., Adjustable strap tension and length
Stainless Steel Top and Rust resistance Spares

Specifications:

Power supply	230v. A.C (Single ph).	
Strapping speed	1.5 Second / Strap	
Max. packing size	Any size	
Minimum packing size	60mm	
Machine dimensions (LxWxH)mm	895 x 565 x 740	895 x 565 x 505
Max. packing weight	60kg	
Max. tension	40kg	
Power consumption	1/3 H.P. Single induction	
Strap width	6 mm to 15 mm	
Machine Weight	90kg Approx	85kg Approx

Applications: Boxes, Textile, Machine can align with In-feed-out-feed.
Conveyor due to its low table height.





Inkjet Printer Machine



L- Sealer With Shrink Tunnel



Chamber shrink wrapping M/C



Currency Note Banding Machine



Carton Tapping Machine



Fully Box Strapping Machine



Fully Auto Coding Machine



Cup / Tray Sealing Machine



**Pneumatic Operated
Strapping Tools**




Self Adhesive (BOPP) Tapes



Stretch Film Rolls



Strapping Roll / Pet Strap



DIVYA
PACKAGING MACHINERY

MANUFACTURERS AND SUPPLIERS OF PACKAGING MACHINERY

Office :

SHED NO. 12, KALP INDUSTRIAL ESTATE, OPP. HP PETROL PUMP,
NEAR SAHITYA BUSINESS PARK, NIKOL RING ROAD, AHMEDABAD -382350

EMAIL: divyapackaging77@gmail.com

Contact No. 9904189177- 8200984237

Website: <https://divyapackagingmachinery.com>